

URINALS

Siphonic urinal CAPRINO PLUS

84206.2



TECHNICAL DATA

Order no.	84206.2
Certified to	EN 13407
Specification	1-l flushing siphonic urinal only in combination with fixing set order no. 89280.8 Charge 000 – without fly
Special specification	Charge 400 – with fly
Water inlet	external
Outlet	horizontal or vertical
Flushing	1 l
Flushing rate	minimum 0.3 l/s
Weight	20,0 kg
Mounting acc. incl.	Wall fixing set M8 LAUFEN, order no. 89280.8
Mounting acc. excl.	vertical inlet connection, order no. 89900.7 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), order no. 89418.1 2-litre siphon with horizontal outlet DN 40 (standard UK), order no. 89418.3 1-litre siphon with horizontal and vertical outlet DN 50 SH 50 (standard Europe, except CH and UK), order no. 89583.9

Mounting acc. excl.	1-litre siphon with horizontal and vertical outlet DN 40 SH 50 (standard CH), order no. 89584.0 Stone screw fixing set M8 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4
---------------------	---

Colours see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-CAPRINO PLUS, sanitary ceramic
EN 13407, dimensions 320 x 350 x 645 mm

1-l flush, water inlet external, outlet horizontal or vertical,
flushing rate minimum 0.3 l/s

Special feature: Vacuum and performance tested

Further options / accessories: Surface refinement LCC (only white), with fly,
horizontal inlet connection, 1-litre siphon with horizontal outlet DN 50
(standard Europe, except CH and UK), 2-litre siphon with horizontal
outlet DN 40 (standard UK), 1-litre siphon with horizontal and vertical
outlet DN 50 SH 50 (standard Europe, except CH and UK) and outlet
DN 40 SH 50 (standard CH)

Order no. 84206.2

TECHNICAL DRAWINGS / S 1 : 20

